



Filter Data Sheet

Water Grade BB - Size Polypropylene Meltblown Cartridge - GWTB

- Unique & production process delivers efficiency, life and economy
- Excellent compatibility with a wide range of chemicals
- Graded density pore structure enhances dirt holding capacity
- Easy cartridge incineration and disposal
- All polypropylene construction

Cross - Reference

Pentek:

DGD2501 = GWTB1

DGD5005 = GWTB5

DGD7525 = GWTB25

GE:

LD01 = GWTB1

LD05 = GWTB5

LD10 = GWTB10

LD20 = GWTB20

LD30 = GWTB30

LD50 = GWTB50

Performance Specifications

Micron Ratings:

1, 3, 5, 10, 20, 25, 30, 50, 75, 100

Efficiencies:

80%

Purity

GWTB series cartridges are free of additives, wetting agents, binders, and silicone.



Construction Materials

Filtration Media.....Polypropylene

Dimensions (Nominal)

Length.....10 & 20 inches

Outside Diameter.....4.5 inches

Inside Diameter.....1 inch

FDA Listed Materials

Manufactured from materials which are listed for food contact applications in Title 21 of the U.S. Code of Federal Regulations.

Maximum Recommended Operating Conditions

Forward.....35 PSID

Reverse.....25 PSID

Change Out Differential Pressure.....20 PSID

Temperature.....140°F (60°C)

Liquid Flow Specifications (Based on 10" Cartridges)

Micron	GPM/PSID
1, 3, 5.....	10
10, 20, 25, 30.....	12
50, 75, 100.....	15

Ordering Information

GWTB	Micron Rating	BB	Length
Water Grade	1	3 BB = 4.5" OD	10
	5	10	20
	20	25	
	30	50	
	75	100	

3725 Interpark Drive • Colorado Springs, CO 80907

Phone: 719-260-5694 • Fax: 719-260-5944 • www.optimumfilter.com